Slimline surface mounted luminaire SQL-PV 1.. OS, direct distribution for T16 lamps

Design: Single luminaire for pendant mounting or direct mounting on the fixing surface. Extremely narrow luminaire housing made of extruded aluminium, end components in sheet steel. Integrated parabolic reflector for optical control and to improve efficiency. The luminaire has a titanium colour powder coating.
With electronic multiwatt electronic ballast 220-240 V, 0/50-60 Hz.

Mounting: The luminaires of series SQL-PV 1 are suitable for direct mounting on the fixing surface or for ceiling pendant mounting using wire pendants. A variety of fixing kits are available (see accessories).

SQL-PV 1.. OS-TI
Opal light profile with silk matt surface in acrylic (PMMA).

SQL-PV 1.. SG-TI
Parabolic SG mirror louvre made of high-reflectance specular anodised super-purity aluminium.

SQL-PV 1.. SM-TI
Parabolic SM mirror louvre made of high-reflectance matt anodised super-purity aluminium.

SQL-PV ...



Voltage: 230V/50Hz
Protection class: IP 20
Approvals:

IP20 T16

SQL-PV 1.. OS-TI

SQL-PV 1.. SG-TI

SQL-PV 1.. SM-TI

Model	Lamps	Dimens. [mm] L	A1	A2	magnetic ballast Prod. code	electronic ballast Prod. code	dimm. ballast (DALI) Prod. code
SQL-PV 121/39 OS-TI	1xT16 21/39 W	1644	1480	820		0626640TI	
SQL-PV 128/54 OS-TI	1xT16 28/54 W	1944	1780	1120		0626641TI	
SQL-PV 121/39 SG-TI	1xT16 21/39 W	1644	1480	820		0626708TI	
SQL-PV 128/54 SG-TI	1xT16 28/54 W	1944	1780	1120		0626709TI	
SQL-PV 121/39 SM-TI	1xT16 21/39 W	1644	1480	820		0626710TI	
SQL-PV 128/54 SM-TI	1xT16 28/54 W	1944	1780	1120		0626711TI	

Accessories

Model	Description	Prod. code
DAD-TI	Titanium ceiling outlet box for power supply 3 x 1.5 mm²	0201636TI
SQL-PVBV	Connecting strip	0207923
ZAL 3x0,75/1,5M-T	Clear mains cable, 3x0.75mm², 1.5 metre	0203579
ZAL 5x0,75/1,5M-T	Clear mains cable, 5x0.75mm², 1.5 metre	0203580
N ZDBE	Rectangular cover, white, for 'Y' wire pendant ZUSP&UKNS	0204332
N ZDBE-TI	Rectangular cover, titanium, for 'Y' wire pendant, ZUSP&UKNS	0204332TI
N ZIDV-SQL-PV 21/3/1,5	Through wiring T16-21/39W, 3x1.5mm²	0208045
N ZIDV-SQL-PV 21/5/1,5	Through wiring T16-21/39W, 5x1.5mm²	0208047
N ZIDV-SQL-PV 28/3/1,5	Through wiring T16-28/54W, 3x1.5mm²	0208046
N ZIDV-SQL-PV 28/5/1,5	Through wiring T16-28/54W, 5x1.5mm²	0208048
ZSPT2Z 120	'Y' wire suspens. kit with ceiling fixture, cyl, 1.5 m, 1 pc	0203582
ZSPT2ZE 120	Y' wire susp. kit with rectangular cover, cyl. 1.5m, 1 pc	0202895
ZWL 3x1,5/1M-SW	Black spiral cable, 3 x 1.5 mm², L=1.0m	0203251

Note One wire or tube pendant must be ordered per suspension point.