

F-LINE for T16 lamps

F-LINE 314/24, F-LINE 414/24

Design: Single luminaire designed for pendant mounting with low-profile luminaire housing. Housing with seamless underside, in edged sheet steel, white or silver colour powder coated.

F-LINE 314/24 with 3 separate light chambers separated by longitudinal webs in the luminaire housing.
2 perforated strips in the luminaire housing between the direct light components, lined with a light filter and backlit.
F-LINE 414/24 with 2 separate light chambers separated by a longitudinal web in the luminaire housing.
2 perforated strips in the luminaire housing between the direct light components, lined with a light filter and backlit.
With electronic multiwatt ballast (MW-EVG) 220-240 V, 0/50-60 Hz.

Mounting: The luminaires are suitable for pendant wire mounting or using accessories for direct ceiling mounting.

F-LINE ... O


Opal profile cover made of UV-resistant acrylic (PMMA) with satinised surface.

F-LINE ... SG

Parabolic mirror louvre SG constructed of high-reflectance, specular, super-purity anodised aluminium

F-LINE ... SM

Parabolic mirror louvre SM constructed of silk matt, super-purity anodised aluminium



Voltage: 230V/50Hz
Protection class: IP 20
acc. to VDE 0711/0875



F-LINE ... O



F-LINE ... SG



F-LINE ... SM



Model	Lamps	Dimens. [mm]				magnetic ballast Prod. code	electronic ballast Prod. code	dimm. ballast (DALI) Prod. code
		L	B1	A1	B			
F-LINE 314 O	3xT16 14 W	653	610	570	650		0626743	0636743
F-LINE 314 O-SI	3xT16 14 W	653	610	570	650		0626743SI	0636743SI
F-LINE 324 O	3xT16 24 W	653	610	570	650		0626748	0636748
F-LINE 324 O-SI	3xT16 24 W	653	610	570	650		0626748SI	0636748SI
F-LINE 314 SG	3xT16 14 W	653	610	570	650		0626741	0636741
F-LINE 314 SG-SI	3xT16 14 W	653	610	570	650		0626741SI	0636741SI
F-LINE 324 SG	3xT16 24 W	653	610	570	650		0626746	0636746
F-LINE 324 SG-SI	3xT16 24 W	653	610	570	650		0626746SI	0636746SI
F-LINE 414 SG	4xT16 14 W	653	610	570	650		0626744	0636744
F-LINE 414 SG-SI	4xT16 14 W	653	610	570	650		0626744SI	0636744SI
F-LINE 424 SG	4xT16 24 W	653	610	570	650		0626749	0636749
F-LINE 424 SG-SI	4xT16 24 W	653	610	570	650		0626749SI	0636749SI
F-LINE 314 SM	3xT16 14 W	653	610	570	650		0626742	0636742
F-LINE 314 SM-SI	3xT16 14 W	653	610	570	650		0626742SI	0636742SI
F-LINE 324 SM	3xT16 24 W	653	610	570	650		0626747	0636747
F-LINE 324 SM-SI	3xT16 24 W	653	610	570	650		0626747SI	0636747SI
F-LINE 414 SM	4xT16 14 W	653	610	570	650		0626745	0636745
F-LINE 414 SM-SI	4xT16 14 W	653	610	570	650		0626745SI	0636745SI
F-LINE 424 SM	4xT16 24 W	653	610	570	650		0626750	0636750
F-LINE 424 SM-SI	4xT16 24 W	653	610	570	650		0626750SI	0636750SI

Accessories

Model	Description	Prod. code
F-LINE-A 314/414 SI	F-LINE 3/414 cover for ceiling mounting, silver, 0% ind comp	0207960SI
F-LINE-A 314/414	F-LINE 3/414 cover for ceiling mounting, white, 0% ind comp	0207960
F-LINE-A20 314/414 SI	F-LINE 3/414 cover for ceiling mount g, silver, 20% ind comp	0207965SI
F-LINE-A20 314/414	F-LINE 3/414 cover for ceiling mounting, white, 20% ind comp	0207965
F-LINE-AS 314/414 SI	F-LINE 3/414 cover with clear diffuser, silver	0207970SI
F-LINE-AS 314/414	F-LINE 3/414 cover with clear diffuser, white	0207970
ZAL 3x0,75/1,5M-T	Clear mains cable, 3x0.75mm ² , 1.5 metre	0203579
ZAL 3x1,5/1,5M-T	Clear mains cable, 3x1.5mm ² , 1.5 metre	0207977
ZAL 5x0,75/1,5M-T	Clear mains cable, 5x0.75mm ² , 1.5 metre	0203580
ZAL 5x1,5/1,5M-T	Clear mains cable, 5x1.5mm ² , 1.5 metre	0207978
ZKF 3X0.75 - 1.0M	Cable guide C-profile, for dia. 4-5mm, 1 metre, transparent	0207979
ZSP	Wire susp. kit with ceiling fixture, wire clamp 1.5m, 1 pc	0205017
ZSPS	Wire suspension kit, screw clamp 1.5m, 1 pc	0205018

Note: One wire or tube pendant must be ordered per suspension point.

